

8 WAY RF/ASI TO 8 MPTS IP GATEWAY

FEATURES:

- Suitable for DVB and Ethernet
- Integrated with demodulation and gateway function
- Support 8 digital channel tuners or 8 ASI input and 8 IP output
- Support MPEG-2 and MPEG-4 TS to IP one-way conversion
- Support BISS descrambling, Mode 1 and E (max up to 512 PID)
- 1 GE output, support parallel 1 Gbps data output channel
- LCD display and control setting on front panel
- Support Web NMS



TECHNICAL SPECIFICATIONS:

| Model | | IPG-DS808R | IPG-DC808R | IPG-DT808R | IPG-IT808R | IPG-AT808R | IPG-SI808R |
|---------------------|----------------------|--|---|---------------------------------|--------------------------------|---------------------------|------------|
| Input section (RF) | Number of input | 8 | | | | | |
| | Standard | DVB-S/S2 950~2150MHz 1~45M/s QPSK, 8PSK | DVB-C 30~1000MHz 16/32/64/128/ 256 QAM | DVB-T/T2 30~999MHz 6/7/8M | ISDB-T 153~862MHz 6/7/8M | ATSC-T 54~858MHz 6M | ASI |
| | RF loop-out loss | -1dB | | | | | |
| | Connector | F type (75Ω) | | | | | |
| Output section (IP) | Number of output | 8 | | | | | |
| | Output | 8 MPTS over UDP protocol, unicast and multicast, RJ45 port | | | | | |
| | Bit-rate | 800Mbps (max total) | | | | | |
| General | Mains supply voltage | AC100V ~ 240V, 50/60Hz | | | | | |
| | Consumption | 20W | | | | | |
| | Dimensions | 44mm(H) x 482mm(W) x 410mm(D) | | | | | |
| | Weight | 4kg | | | | | |
| | Temperature | 0~45°C (operating), -20~80°C (storage) | | | | | |